


NASA/CR-2002-211657
ICASE Report No. 2002-17



Lattice Boltzmann Method for 3-D Flows with Curved Boundary

Renwei Mei, Wei Shyy, and Dazhi Yu
University of Florida, Gainesville, Florida

Li-Shi Luo
ICASE, Hampton, Virginia



June 2002

Report Documentation Page

Report Date 00JUN2002	Report Type N/A	Dates Covered (from... to) -
Title and Subtitle Lattice Boltzmann Method for 3-D Flows with Curved Boundary		Contract Number
		Grant Number
		Program Element Number
Author(s) Renwei Mei, Wei Shyy, and Dazhi Yu, Li-Shi Luo		Project Number
		Task Number
		Work Unit Number
Performing Organization Name(s) and Address(es) ICASE Mail Stop 132C NASA Langley Research Center Hampton, VA 23681-2199		Performing Organization Report Number
Sponsoring/Monitoring Agency Name(s) and Address(es)		Sponsor/Monitor's Acronym(s)
		Sponsor/Monitor's Report Number(s)
Distribution/Availability Statement Approved for public release, distribution unlimited		
Supplementary Notes ICASE Report No. 2002-17		
Abstract see report		
Subject Terms		
Report Classification unclassified	Classification of this page unclassified	
Classification of Abstract unclassified	Limitation of Abstract SAR	
Number of Pages 23		

The NASA STI Program Office . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the lead center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers, but having less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.
- **CONFERENCE PUBLICATIONS.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized data bases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- Email your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA STI Help Desk at (301) 621-0134
- Telephone the NASA STI Help Desk at (301) 621-0390
- Write to:
NASA STI Help Desk
NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076-1320

NASA/CR-2002-211657
ICASE Report No. 2002-17



Lattice Boltzmann Method for 3-D Flows with Curved Boundary

Renwei Mei, Wei Shyy, and Dazhi Yu
University of Florida, Gainesville, Florida

Li-Shi Luo
ICASE, Hampton, Virginia

ICASE
NASA Langley Research Center
Hampton, Virginia

Operated by Universities Space Research Association



Prepared for Langley Research Center
under Contract NAS1-97046

June 2002

Available from the following:

NASA Center for AeroSpace Information (CASI)
7121 Standard Drive
Hanover, MD 21076-1320
(301) 621-0390

National Technical Information Service (NTIS)
5285 Port Royal Road
Springfield, VA 22161-2171
(703) 487-4650

LATTICE BOLTZMANN METHOD FOR 3-D FLOWS WITH CURVED BOUNDARY

RENWEI MEI*, WEI SHYY†, DAZHI YU‡, AND LI-SHI LUO§

Abstract. In this work, we investigate two issues that are important to computational efficiency and reliability in fluid dynamics applications of the lattice Boltzmann equation (LBE): (1) Computational stability and accuracy of different lattice Boltzmann models and (2) the treatment of the boundary conditions on curved solid boundaries and their 3-D implementations. Three athermal 3-D LBE models (D3Q15, D3Q19, and D3Q27) are studied and compared in terms of efficiency, accuracy, and robustness. The boundary treatment recently developed by Filippova and Hänel and Mei *et al.* in 2-D is extended to and implemented for 3-D. The convergence, stability, and computational efficiency of the 3-D LBE models with the boundary treatment for curved boundaries were tested in simulations of four 3-D flows: (1) Fully developed flows in a square duct, (2) flow in a 3-D lid-driven cavity, (3) fully developed flows in a circular pipe, and (4) a uniform flow over a sphere. We found that while the fifteen-velocity 3-D (D3Q15) model is more prone to numerical instability and the D3Q27 is more computationally intensive, the D3Q19 model provides a balance between computational reliability and efficiency. Through numerical simulations, we demonstrated that the boundary treatment for 3-D arbitrary curved geometry has second-order accuracy and possesses satisfactory stability characteristics.

Key words. lattice Boltzmann method, boundary condition for curved geometries, accuracy, 3-D flows, Navier-Stokes equations

Subject classification. Fluid Dynamics

1. Introduction.

1.1. Basic Notion of the Lattice Boltzmann Equation. In one fashion or another, conventional methods of computational fluid dynamics (CFD) compute pertinent flow fields, such as velocity \mathbf{u} and pressure p , by numerically solving the Navier-Stokes equations in space \mathbf{x} and time t [23, 9, 27]. In contrast, various kinetic methods use the transport equation, or the Boltzmann equation in particular, for various problems in fluid dynamics. The Boltzmann equation deals with the single particle distribution function $f(\mathbf{x}, \boldsymbol{\xi}, t)$, where $\boldsymbol{\xi}$ is the particle velocity, in phase space $(\mathbf{x}, \boldsymbol{\xi})$ and time t . Recently, the method of the lattice Boltzmann equation (LBE) [5, 24, 3, 6] has become an alternative to the conventional CFD methods employing Navier-Stokes equations. The theoretical premises of the LBE method are that (1) hydrodynamics is insensitive to the details of microscopic physics, and (2) hydrodynamics can be preserved so long as the conservation laws and associated symmetries are respected in the microscopic or mesoscopic level. Therefore, the computational advantages of the LBE method are attained by drastically reducing the particle velocity

*Department of Aerospace Engineering, Mechanics & Engineering Science, University of Florida, Gainesville, FL 32611-6250 (email address: rwm@aero.ufl.edu).

†Department of Aerospace Engineering, Mechanics & Engineering Science, University of Florida, Gainesville, FL 32611-6250 (email address: ws@aero.ufl.edu).

‡Department of Aerospace Engineering, Mechanics & Engineering Science, University of Florida, Gainesville, FL 32611-6250 (email address: ydz@aero.ufl.edu).

§ICASE, Mail Stop 132C, NASA Langley Research Center, 3 West Reid Street, Building 1152, Hampton, VA 23681-2199 (email address: luo@icase.edu). This research was supported by the National Aeronautics and Space Administration under NASA Contract No. NAS1-97046 while the author was in residence at ICASE, NASA Langley Research Center, Hampton, VA 23681-2199.

space $\boldsymbol{\xi}$ to only a very few discrete points without seriously degrading hydrodynamics. This is possible because the LBE method rigorously preserves the hydrodynamic moments of the distribution function f , such as mass density and momentum fluxes, and the necessary symmetries [13, 14, 1].

One popular kinetic model is the Boltzmann equation with the single relaxation time approximation [4]:

$$(1.1) \quad \partial_t f + \boldsymbol{\xi} \cdot \nabla f = -\frac{1}{\lambda} [f - f^{(0)}],$$

where $\boldsymbol{\xi}$ is the particle velocity, $f^{(0)}$ is the equilibrium distribution function (the Maxwell-Boltzmann distribution function), and λ is the relaxation time. The mass density ρ and momentum density $\rho \mathbf{u}$ are the first $(D+1)$ hydrodynamic moments of the distribution function f and $f^{(0)}$, where D is the dimension of velocity space.

To solve for f numerically, Eq. (1.1) is first discretized in the velocity space $\boldsymbol{\xi}$ using a finite set of velocities $\{\boldsymbol{\xi}_\alpha\}$ without affecting the conserved hydrodynamic moments [13, 14, 1],

$$(1.2) \quad \partial_t f_\alpha + \boldsymbol{\xi}_\alpha \cdot \nabla f_\alpha = -\frac{1}{\lambda} [f_\alpha - f_\alpha^{(0)}].$$

In the above equation, $f_\alpha(\mathbf{x}, t) = f(\mathbf{x}, \boldsymbol{\xi}_\alpha, t)$ and $f_\alpha^{(0)}(\mathbf{x}, t) = f^{(0)}(\mathbf{x}, \boldsymbol{\xi}_\alpha, t)$ are the distribution function and the equilibrium distribution function of the α -th discrete velocity $\boldsymbol{\xi}_\alpha$, respectively. The nine-velocity (or 9-bit) LBE model on the 2-D square lattice, denoted as D2Q9 model, has been widely used for simulating 2-D flows. For 3-D flows, there are several cubic lattice models, such as the fifteen-velocity (D3Q15), nineteen-velocity (D3Q19), and twenty-seven-velocity (D3Q27) models [12], which have been used in the literature. All three models have a rest particle (with zero velocity) in the discretized velocity set $\{\boldsymbol{\xi}_\alpha\}$. A minor variation of those models is to remove the rest particles from the discrete velocity set; the resulting models are known as the D3Q14, D3Q18, and D3Q26 models, respectively. The LBE models with a rest particle generally have better computational stability. For athermal fluids, the equilibrium distributions for D2Q9, D3Q15, D3Q19, and D3Q27 models are all of the form [14]

$$(1.3) \quad f_\alpha^{(eq)} = w_\alpha \rho \left[1 + \frac{3}{c^2} \mathbf{e}_\alpha \cdot \mathbf{u} + \frac{9}{2c^4} (\mathbf{e}_\alpha \cdot \mathbf{u})^2 - \frac{3}{2c^2} (\mathbf{u} \cdot \mathbf{u}) \right],$$

where w_α is a weighting factor and \mathbf{e}_α is a discrete velocity, $c = \delta x / \delta t$ is the lattice speed, and δx and δt are the lattice constant and the time step, respectively. (The values of the weighting factor w_α for D3Q15, D3Q19, and D3Q27 models and the diagrams illustrating the lattice structure for D3Q15 and D3Q19 models are given in the Appendix.) It can be shown that $f_\alpha^{(eq)}$ is in fact a Taylor series expansion of the Maxwellian $f_\alpha^{(0)}$ [13, 14]. This approximation of $f_\alpha^{(0)}$ by the above $f_\alpha^{(eq)}$ makes the method valid only in the incompressible limit $u/c \rightarrow 0$.

With the velocity space discretized, the hydrodynamic moments of f and $f^{(0)}$ are evaluated by the following quadrature formulas:

$$(1.4a) \quad \rho = \sum_\alpha f_\alpha = \sum_\alpha f_\alpha^{(0)},$$

$$(1.4b) \quad \rho \mathbf{u} = \sum_\alpha \mathbf{e}_\alpha f_\alpha = \sum_\alpha \mathbf{e}_\alpha f_\alpha^{(0)}.$$

The speed of sound of the above 3-D LBE models is $c_s = c/\sqrt{3}$ and the equation of state is that of an ideal gas $p = \rho c_s^2$. The viscosity of the fluid is $\nu = \lambda c_s^2$.

Equation (1.2) is often discretized in space \mathbf{x} and time t into

$$(1.5) \quad f_\alpha(\mathbf{x}_i + \mathbf{e}_\alpha \delta t, t + \delta t) + f_\alpha(\mathbf{x}_i, t) = -\frac{1}{\tau} [f_\alpha(\mathbf{x}_i, t) - f_\alpha^{(0)}(\mathbf{x}_i, t)],$$

where $\tau = \lambda/\delta t$. This is the lattice Boltzmann equation with the Bhatnagar-Gross-Krook (BGK) approximation [4] and is often referred to as the LBGK model [5, 24]. The viscosity in the NS equation derived from Eq. (1.5) is

$$(1.6) \quad \nu = (\tau - 1/2)c_s^2\delta t.$$

This choice for the viscosity makes the LBGK scheme formally a second order method for solving incompressible flows [14]. The positivity of the viscosity requires that $\tau > 1/2$. Equation (1.5) can be solved in the following two steps:

$$(1.7a) \quad \text{collision step:} \quad \tilde{f}_\alpha(\mathbf{x}_i, t) = f_\alpha(\mathbf{x}_i, t) - \frac{1}{\tau} \left[f_\alpha(\mathbf{x}_i, t) - f_\alpha^{(0)}(\mathbf{x}_i, t) \right],$$

$$(1.7b) \quad \text{streaming step:} \quad f_\alpha(\mathbf{x}_i + \mathbf{e}_\alpha \delta t, t + \delta t) = \tilde{f}_\alpha(\mathbf{x}_i, t),$$

where \tilde{f}_α denotes the post-collision state of the distribution function. It is noted that the collision step is completely local, and the streaming step is uniform and requires little computational effort. Equation (1.7) is explicit, easy to implement, and straightforward to parallelize.

1.2. Boundary Condition on a Solid Surface. To date, most Neumann type boundary conditions for a solid boundary used in the LBE method are based upon the bounce-back boundary condition: A particle colliding with a stationary wall simply reverses its momentum. Much of the previous work on LBE boundary conditions is devoted to the analysis and improvement of the bounce-back boundary condition [29, 10, 17, 2, 22, 7, 11, 15, 19, 30]. The bounce-back boundary condition can attain second-order accuracy if the boundary is fictitiously placed half-way between two nodes. That is, the second-order accuracy of the bounce-back boundary condition can only be achieved when the boundaries are located right in the middle of two neighboring lattices [$\Delta = 0.5$; see Eq. (1.8)]. (Readers are referred to our recent work [20] for a summary of the previous work.) This prevents the direct application of the bounce-back type boundary conditions to simulate a solid body with smooth curvature. To circumvent this difficulty, Mei & Shyy solved Eq. (1.2) in curvilinear coordinates using a finite difference method to solve for \tilde{f}_α [21]. One can also use body-fitted curvilinear coordinates with interpolation throughout the entire mesh, except at the boundaries where the bounce-back boundary condition is used [12]. In more recent works [8, 20], Cartesian coordinates are adopted with interpolation used only at the boundaries. These techniques rely on the freedom of using interpolation techniques. We used the latter technique in the present work.

As shown in Fig. 1 for a 2-D projection involving a 3-D body, the streaming step requires the knowledge of $\tilde{f}_\alpha(\mathbf{x}_b, t)$, in which $\mathbf{e}_\alpha = -\mathbf{e}_\alpha$, at \mathbf{x}_b on the solid side in order to compute $\tilde{f}_\alpha(\mathbf{x}_f, t)$ for the lattice node located on the fluid side at $\mathbf{x}_f = \mathbf{x}_b + \mathbf{e}_\alpha \delta t$. Defining

$$(1.8) \quad \Delta = \frac{\|\mathbf{x}_f - \mathbf{x}_w\|}{\|\mathbf{x}_f - \mathbf{x}_b\|}$$

as the fraction of an intersected link in the fluid region, it is seen that $0 \leq \Delta \leq 1$ and the horizontal or vertical distance between \mathbf{x}_b and \mathbf{x}_w is $(1 - \Delta)\delta x$ on the cubic lattice.

Based on the work of Filippova and Hänel [8], hereinafter referred to as FH, Mei *et al.* [20] proposed the following treatment for on curved boundaries,

$$(1.9) \quad \tilde{f}_\alpha(\mathbf{x}_b, t) = (1 - \chi)\tilde{f}_\alpha(\mathbf{x}_f, t) + \chi f_\alpha^{(*)}(\mathbf{x}_b, t) + 2w_\alpha \rho \frac{3}{2c^2} \mathbf{e}_\alpha \cdot \mathbf{u}_w$$

with

$$(1.10) \quad f_\alpha^{(*)}(\mathbf{x}_b, t) = w_\alpha \rho \left[1 + \frac{3}{c^2} \mathbf{e}_\alpha \cdot \mathbf{u}_{bf} + \frac{9}{2c^4} (\mathbf{e}_\alpha \cdot \mathbf{u}_f)^2 - \frac{3}{2c^2} (\mathbf{u}_f \cdot \mathbf{u}_f) \right],$$

proposed boundary conditions along with the selected LBE models.

2. Modification of the Boundary Condition for $\Delta > 1/2$. Equations (1.9) – (1.11) are first applied to a fully developed pressure driven 2-D channel flow by using the 3-D LBE model D3Q19. At the inlet ($i = 1$) and exit ($i = N_x$, in which N_x is the number of lattices in the x -direction) the following zero derivative condition is imposed after the collision step,

$$(2.1a) \quad \tilde{f}_\alpha(i = 1, j, k) = \tilde{f}_\alpha(i = 2, j, k),$$

$$(2.1b) \quad \tilde{f}_\alpha(i = N_x, j, k) = \tilde{f}_\alpha(i = N_x - 1, j, k).$$

At $k = 1$ and $k = N_z$, the same is imposed,

$$(2.2a) \quad \tilde{f}_\alpha(i, j, k = 1) = \tilde{f}_\alpha(i, j, k = 2),$$

$$(2.2b) \quad \tilde{f}_\alpha(i, j, k = N_z) = \tilde{f}_\alpha(i, j, k = N_z - 1).$$

The constant pressure gradient ∇p along the x -direction is treated as a body force and is included in the solution procedure after the collision step and the enforcement of the above zero-derivative conditions as:

$$(2.3) \quad \tilde{f}_\alpha(\mathbf{x}_i, t) = \tilde{f}_\alpha(\mathbf{x}_i, t) - w_\alpha \frac{3}{c^2} \frac{dp}{dx} \mathbf{e}_\alpha \cdot \hat{\mathbf{x}},$$

where $\hat{\mathbf{x}}$ is the unit vector along the x -axis. On the solid walls ($y = 0$ and $y = H$), Eqs. (1.9) – (1.11) are used. The exact solution for the velocity is used as the velocity initial condition. The equilibrium distribution $f_\alpha^{(eq)}$ function based on the exact solution for the velocity profile is used as the initial condition for f_α . The pressure gradient is set to $\frac{dp}{dx} = -1.0 \times 10^{-6}$. All computations are carried out using double precision.




FIG. 2. Stability boundary of FH's scheme in a square duct flow for Δ near 1. Shaded areas under stability boundaries are unstable regions.

It was found that the computations are stable for τ close to 0.5 (for example, $\tau = 0.505$) as long as Δ is not too close to unity (for example, $\Delta \leq 0.87$). When Δ is equal to 1, stable computation can only be carried out for τ no smaller than 0.6. Fig. 2 shows the stability bound for the channel flow simulation with a system size $N_x \times N_y \times N_z = 5 \times 35 \times 5$, near $\Delta = 1$. Also shown by the dashed line is the stability-instability

boundary for the channel flow simulation using D2Q9 model and with a system size $N_x \times N_y = 5 \times 35$, near $\Delta = 1$. It is clear that similar behavior exists in both 2-D and 3-D channel flow simulations. When the computation for the pressure driven flow in a square duct was carried out using the D3Q19 formulation, a similar stability bound was encountered.

Ideally, one would like to use a fixed value of τ for the entire range of $0 \leq \Delta \leq 1$ in a simulation. Computational stability would then require the use of τ around 0.6, instead of a value that is close to 0.5, which makes it difficult to simulate a lower viscosity, or higher Reynolds number flow. To overcome the restriction imposed by the numerical stability requirement due to interpolation, it would be useful if one could decrease the value of $\chi = (2\Delta - 1)/\tau$ given by Eq. (1.11a). This can be accomplished by using

$$(2.4) \quad \mathbf{u}_{bf} = \left(1 - \frac{3}{2\Delta}\right) \mathbf{u}_f + \frac{3}{2\Delta} \mathbf{u}_w \quad \text{and} \quad \chi = \frac{2\Delta - 1}{\tau + 1/2} \quad \text{for } \Delta \geq 1/2.$$

That is, the velocity \mathbf{u}_{bf} is evaluated at $(\mathbf{x}_b + \mathbf{e}_\alpha/2)$, instead of at \mathbf{x}_b , using the information at \mathbf{x}_f and \mathbf{x}_w through linear extrapolation.

With Eq. (2.4) replacing Eq. (1.11a), the channel flow simulations using D3Q19 lattice model are carried out again for Δ from 0.85 to 1.0. Satisfactory results for the velocity profiles are obtained for $\tau = 0.505$ with $N_x \times N_y \times N_z = 5 \times 35 \times 5$ in terms of computational stability. For $\Delta < 0.85$, the accuracy of the solutions using Eqs. (1.11a) and (2.4) is the same when the computations are stable.

3. Results and Discussions.

3.1. Fully Developed Flow in a Square Duct. For fully developed flow inside a square duct of height H defined by the region $-a \leq y \leq a$, and $-a \leq z \leq a$, where $a = H/2$, the axial velocity profile can be found in Ref. [28, p. 123]:

$$(3.1) \quad u_x(y, z) = \frac{16a^2}{\mu\pi^3} \left(-\frac{dp}{dx}\right) \sum_{k=0}^{\infty} (-1)^k \left[1 - \frac{\cosh\left(\frac{(2k+1)\pi z}{2a}\right)}{\cosh\left(\frac{(2k+1)\pi}{2}\right)}\right] \frac{\cosh\left(\frac{(2k+1)\pi y}{2a}\right)}{(2k+1)^3}.$$

Figure 3 compares the exact axial velocity profiles at $z = 0$ and the LBE-based solution with $\Delta = 0.2$ and $H = 2a = 32.4$. A total of $N_x \times N_y \times N_z = 13 \times 35 \times 35$ grid points are used. The pressure gradient is $\frac{dp}{dx} = -1.0 \times 10^{-6}$ and $\tau = 0.52$. The nineteen-velocity model is used in the simulations. Excellent agreement was obtained.

Figure 4a shows the dependence of relative L_2 -norm error,

$$(3.2) \quad E_2 = \sqrt{\frac{\int_0^H \int_0^H [u_{\text{LBE}}(y, z) - u_{\text{exact}}(y, z)]^2 dy dz}{\int_0^H \int_0^H [u_{\text{exact}}(y, z)]^2 dy dz}},$$

on the duct height or the lattice resolution $H = N_y - 3 + 2\Delta$. The integral is evaluated by the trapezoidal rule. As was demonstrated by Mei *et al.* [20], the boundary treatment results in second order convergence for 2-D channel flow. Fig. 4a clearly shows that the total error (from both the flow field and the boundary condition) of the LBE solution in 3-D flow decays quadratically.

Figure 4b shows the relative L_2 -norm error E_2 as a function of Δ in the duct flow using $13 \times 35 \times 35$ grid points and $\tau = 0.52$. For the purpose of comparison, the relative L_2 -norm error in the 2-D channel flow simulation using the D2Q9 model with $N_y = 35$ and $\tau = 0.52$ is also shown. The relative error is larger in




FIG. 3. Comparison of axial velocity profiles in a pressure-driven square duct flow at $z = 0$ between the exact solution (solid line) and the LBE solution (dashed line) with $\Delta = 0.2$, $dp/dx = -1.0 \cdot 10^{-6}$, $\tau = 0.52$, and $H = 32.4$.

3-D duct flow than in the 2-D channel flow. Nevertheless, the error exhibits the same qualitative behavior in both 2-D and 3-D as a function of Δ .

It should be noted that the accuracy of the D2Q9 model and the D3Q19 model is different in the sense that beyond the conserved moments (density and momentum in athermal fluids), these two models have different accuracy in preserving higher order moments (fluxes) [13, 14]. The D2Q9 model preserves all the moments up to the second order in momentum space, which include momentum fluxes, and maintains the isotropy of these moments, whereas the D3Q19 model can preserve density and momentum, but cannot maintain the same accuracy and isotropy of the fluxes as the D2Q9 model. The only 3-D equivalent of the D2Q9 model in terms of accuracy of the moments is the D3Q27 model [13, 14].

3.2. Simulation Results for 3-D Lid-Driven Cavity Flows. Lid-driven cavity flow has been studied extensively in the CFD community. Most research has been focused on 2-D problems. Limited numbers of reliable numerical results for steady state 3-D cavity flows have been obtained in the past several years. In this study, the multi-block finite difference solution of the NS equations obtained recent by Salom [26] is used to compare with the present LBE based results.

The size of the cavity is H^3 , the number of grid is $N_x \times N_y \times N_z$, and $N_x = N_y = N_z$. The driving lid is placed at $y = H$, moving along the direction of x -axis with a speed $U = 0.1$ in lattice units. Figure 5a compares profiles of horizontal velocity $u_x(y)$ obtained using $33 \times 33 \times 33$ lattices with the solution to the NS equations at $x/H = z/H = 0.5$ for $Re = 400$. All three LBE models (D3Q15, D3Q19, and D3Q27) are used. For the fifteen-velocity model, the computation becomes unstable and blows up at this Reynolds number with 33^3 lattice resolution and $\Delta = 0.5$. For $\Delta = 0.5$, the nineteen-velocity model and the twenty-seven-velocity model give very similar $u_x(y)$ profiles and both under-predict slightly the magnitude of the minimum in the profiles. The 19-velocity model is also used with $\Delta = 0.25$; there is a slight overshoot in the velocity profiles in comparison to the results in Ref. [26]. Fig. 5b compares $u_x(y)$ profiles obtained using the fifteen-velocity and 19-velocity lattice models on the 67^3 lattice grids and $\Delta = 0.5$ with the NS solution [26] at $x/H = z/H = 0.5$ for $Re = 400$. Excellent agreement is observed. Clearly, the nineteen-velocity model is




FIG. 4. Error behaviors in a pressure-driven square duct flow with $dp/dx = -1.0 \cdot 10^{-6}$, $\tau = 0.52$. (a) Dependence of the relative L_2 -norm error on the lattice resolution $H = N_y - 3 + 2\Delta$, with $\Delta = 0.2$. The straight line is a least-square fit of the data (symbols) with a slope of -2 . (b) Relative L_2 -norm error as a function of Δ for the 3-D duct flow (solid line) and the 2-D channel flow simulations.

superior to the fifteen-velocity model. Although the fifteen-velocity model requires 21% less CPU time and storage than the nineteen-velocity model per lattice, it is not as robust as the nineteen-velocity model and may actually require more CPU time and memory to obtain a reasonable solution since more lattice points are clearly needed.

It should be noted that stability property of the nineteen-velocity model and the fifteen-velocity model are significantly different. All LBE models have inherent spurious invariants because of their simple dynamics [18]. However, the stability of the LBE models, which is very much affected by these spurious invariants, differs from one model to another, and also depends on other factors such as boundary conditions and the local Reynolds number [18]. Among the three 3-D LBE models (D3Q15, D3Q19, and D3Q27), the D3Q15 model is the least isotropic and therefore is more prone to numerical instability. This is independently verified in a recent work by Kandhai *et al.* [16]. It was observed that the D3Q15 model may induce artificial checkerboard invariants which are the eigenmodes of the linearized LBGK collision operator at wave vector $k = \pi$; this can cause spatial oscillations to develop in the flow field at high Reynolds number [18]. Although it was pointed out that the presence of solid walls can suppress the oscillation in certain cases, the solid




FIG. 5. 3-D lid-driven cavity flow. Normalized horizontal velocity profiles $u_x(x, y, z)/U$ at $x/H = z/H = 0.5$, with $rm Re = 400$, $U = 0.1$. The Navier-Stokes solution (solid line) from Ref. [26] are compared with the following LBE solutions. (a) $N_x \times N_y \times N_z = 33^3$, the nineteen-velocity LBE solutions with $\Delta = 0.5$ (dashed line) and $\Delta = 0.25$ (long dashed line), and the twenty-seven-velocity LBE solutions with $\Delta = 0.5$ (dotted line). (b) $N_x \times N_y \times N_z = 67^3$, the nineteen-velocity (dashed line) and fifteen-velocity (dotted line) LBE solutions with $\Delta = 0.5$.

walls in the present case actually excite the oscillation by producing a shear stress singularity at the two corners between the moving and stationary walls. Clearly, the D3Q19 model is better suited to handle flow singularities than the D3Q15 model in this case.

Figure 6a compares the profiles of transversal velocity $u_y(x)$ obtained from various 3-D LBE models using 33^3 lattices (grids) with the NS solution at $y/H = z/H = 0.5$ for $Re = 400$. For $\Delta = 0.5$ we found that the results from the twenty-seven-velocity model deviate more from the NS results of Ref. [26] than the results of the nineteen-velocity model with the same resolution in the spatial region $0.1 < x/H < 0.6$. Both models under-predict the extrema of the velocity profile compared to the NS solution of Ref. [26]. For $\Delta = 0.25$, the results of the nineteen-velocity model slightly over-predict the extrema, also shown in Fig. 6a. However the difference is relatively smaller in both cases. Figure 6b shows similar results of velocity profile

with a resolution of 67^3 grid points and the same Reynolds number $Re = 400$. With 67^3 lattice resolution, the result of the fifteen-velocity model significantly differs from the result of the nineteen-velocity model and that of the NS solution in Ref. [26]. These comparisons further suggest that the nineteen-velocity model is better than the fifteen-velocity model in terms of accuracy and stability, and better than the twenty-seven-velocity in terms of computational efficiency. The nineteen-velocity model represents a good compromise in terms of both computational efficiency and reliability.




FIG. 6. 3-D lid-driven cavity flow. Normalized transversal velocity profiles $u_y(x, y, z)/U$ at $y/H = z/H = 0.5$, with $Re = 400$, $U = 0.1$. The Navier-Stokes solution (solid line) from Ref. [26] are compared with the following LBE solutions. (a) $N_x \times N_y \times N_z = 33^3$, the nineteen-velocity LBE solutions with $\Delta = 0.25$ (long dashed line) and $\Delta = 0.5$ (dotted line), and the twenty-seven-velocity LBE solution with $\Delta = 0.5$ (dashed line). (b) $N_x \times N_y \times N_z = 67^3$, the nineteen-velocity (dashed line) and fifteen-velocity (dotted line) LBE solutions with $\Delta = 0.5$.

Figures 7 and 8 show the effect of Reynolds number (from 100 to 2000) on the profiles of horizontal velocity $u_x(y)$ and transversal velocity $u_y(x)$ at $x/H = z/H = 0.5$ based on the D3Q19 model. For $Re = 100$, 400 and 1000, $\Delta = 0.5$ is used. It is worth noting that for $Re = 2000$, the system size of 67^3 , $U = 0.1$, and $\tau = 0.50325$, the LBE simulation with $\Delta = 0.5$ eventually becomes unstable, although the steady state result of $Re = 1000$ is used as the initial condition for $Re = 2000$. When $\Delta = 0.25$ is used on the 67^3 lattice system,

no computational instability occurs and the steady state solution is obtained. Weak spatial oscillation in the $u_x(y)$ and $u_y(x)$ velocity profiles was observed for $\text{Re} = 2000$, which indicates that further increase in Re would require better spatial resolution. It is also worth pointing out that when FH's boundary condition [8] is used for $\text{Re} = 2000$ with $\Delta = 0.25$, the solution eventually blows up even when converged results (based on the present boundary condition for $\Delta = 0.25$) at $\text{Re} = 2000$ are used as the initial condition.




FIG. 7. 3-D lid-driven cavity flow. Effect of Reynolds number Re on the normalized horizontal velocity profiles $u_x(x, y, z)/U$ at $x/H = z/H = 0.5$. The results are obtained by using D3Q19 LBE model with $U = 0.1$, $\text{Re} = 100$, $N_x \times N_y \times N_z = 33^3$, $\Delta = 0.5$ (solid line); $U = 0.1$, $\text{Re} = 400$, $N_x \times N_y \times N_z = 67^3$, $\Delta = 0.5$ (dotted line); $U = 0.1$, $\text{Re} = 1000$, $N_x \times N_y \times N_z = 67^3$, $\Delta = 0.5$ (dashed line); and $U = 0.1$, $\text{Re} = 2000$, $N_x \times N_y \times N_z = 67^3$, $\Delta = 0.25$ (long dashed line).




FIG. 8. 3-D lid-driven cavity flow. Effect of Reynolds number Re on the normalized transversal velocity profiles $u_y(x, y, z)/U$ at $y/H = z/H = 0.5$. The results are obtained by using D3Q19 LBE model with $U = 0.1$, $\text{Re} = 100$, $N_x \times N_y \times N_z = 33^3$, $\Delta = 0.5$ (solid line); $U = 0.1$, $\text{Re} = 400$, $N_x \times N_y \times N_z = 67^3$, $\Delta = 0.5$ (dotted line); $U = 0.1$, $\text{Re} = 1000$, $N_x \times N_y \times N_z = 67^3$, $\Delta = 0.5$ (dashed line); and $U = 0.1$, $\text{Re} = 2000$, $N_x \times N_y \times N_z = 67^3$, $\Delta = 0.5$ (long dashed line).

3.3. Fully Developed Flows inside a Circular Pipe. Figure 9 shows the discretized domain and the boundary nodes \mathbf{x}_b (denoted by solid symbols) for flow inside a circular pipe of radius $R = 9.5$ lattice units. Geometrically, the LBE simulation of the pipe flow differs from that of the duct flow in that the fraction of the intersected link Δ is not constant over the entire boundary. As seen in Fig. 4b, computational error can vary with Δ in the duct flow and the difference in the error can easily be as large as a factor of four for $0 \leq \Delta \leq 1$. Furthermore, the error is the smallest when Δ is between 0.3 to 0.6. Hence, it is reasonable to expect that the overall error in the solution will depend on the distribution of Δ in the entire set of Δ .




FIG. 9. Schematic for the boundary nodes \mathbf{x}_b (solid symbols) in yz plane in the pressure-driven in a pipe of radius $R = 9.5$.

Figure 10 shows the relative L_2 -norm error for the axial velocity profile defined as

$$(3.3) \quad E_2 = \sqrt{\frac{\sum_{(y_j, z_k) \in \Omega} [u_{\text{LBE}}(y_j, z_k) - u_{\text{exact}}(y_j, z_k)]^2}{\sum_{(y_j, z_k) \in \Omega} [u_{\text{exact}}(y_j, z_k)]^2}},$$

where Ω is the set of the discrete lattice grids inside the pipe, as a function of radius R for $R = 3.5, 4.5, 5.5, 9.5, 13.5, 18.5$ and 23.5 . The pressure gradient is $\frac{dp}{dx} = -1.0 \times 10^{-6}$ and $\tau = 0.52$. It is noted that each simple summation in Eq. (3.3) is slightly less than the exact integration over the entire circle due to the discretization. To ensure that such a treatment does not affect the qualitative behavior of the error measurement, the centerline axial velocity, u_c , is also compared with the exact solution and the error is defined as:

$$(3.4) \quad E_c = \frac{|u_{c,\text{LBE}} - u_{c,\text{exact}}|}{|u_{c,\text{exact}}|}.$$

It is seen that E_c behaves very similarly to E_2 and both are non-monotonic. This oscillatory behavior could be due to the difference in the distribution of Δ , which in turn results in the difference of the dissipation due to the interpolation around the boundary. Shown also in Fig. 10 is the error E_2 of the square duct flow solution (with $\Delta = 0.2$) as a function of equivalent radius $H/\pi^{1/2}$, which exhibits a quadratic convergence. Despite the non-monotonic behavior, it can still be seen that on average, E_2 and E_c decay quadratically

with increasing radius and the accuracy in the pipe flow simulation is comparable to that in the square duct flow simulation.




FIG. 10. Variation of relative errors E_2 and E_c in velocity profiles as a function of the pipe radius R or the equivalent radius $H/\pi^{1/2}$ for a square duct. Shown are the $E_2(R)$ (\square) and $E_c(R)$ (\diamond) for the pressure-driven pipe flow, and $E_2(H/\pi^{1/2})$ (+) for the pressure-driven square-duct flow. The straight line is a least-square fit of $E_2(H/\pi^{1/2})$ with a slope of -2 .

Figure 11 shows the axial velocity profiles in the pipe for $R = 3.5, 5.5, 9.5$, and 13.5 in comparison with the exact solution. Even for a very small radius $R = 3.5$, the LBE solution agrees with the exact solution remarkably well. A noticeable discrepancy in the velocity profile at $R = 9.5$ is also observed in E_2 and E_c shown in Fig. 10.




FIG. 11. Comparison of the axial velocity profiles between the LBE solutions (dashed lines) and the analytic solutions (solid lines) for the pressure-driven pipe flow. Shown in the figure (from left to right) are solutions with $R = 3.5, 5.5, 9.5$, and 13.5 . $dp/dx = -1.0 \cdot 10^{-6}$, $\tau = 0.52$

3.4. Simulation Results for a Uniform Flow over a Sphere. The conventional LBE scheme uses uniform meshes. Without local mesh refinement, it is difficult to compute the external flow over a blunt body efficiently since a large number of grid points in the far field will be wasted. As a first attempt, the

flow over a sphere is computed within a finite region in the transversal directions.

As shown in Fig. 12, the outer boundary is placed at $y = \pm H/2$ and $z = \pm H/2$. At $y = -H/2$, the lattice is $j = 2$. The boundary conditions at $j = 1$ for f_α 's are given by the following linear extrapolation:

$$(3.5) \quad f_\alpha(i, 1, k) = 2f_\alpha(i, 2, k) - f_\alpha(i, 3, k).$$

The velocity at $j = 2$ is set as

$$(3.6) \quad \mathbf{u}(i, 2, k) = \mathbf{u}(i, 3, k).$$

Similar treatment is applied at $y = +H/2$ and $z = \pm H/2$. The extrapolation condition given by Eqs. (3.5) and (3.6) allow the flow to leave the outer boundary. This helps to reduce the effect of the outer boundary on the flow field and on the drag force. At the inlet, a uniform velocity profile is imposed at $i = 1.5$ (half way between the first and second lattice points) and Eq. (1.9) is applied to obtain the condition for $f_\alpha(1, j, k)$ with $\chi = 0$. At the exit, a simple extrapolation is used,

$$(3.7) \quad f_\alpha(N_x, j, k) = 2f_\alpha(N_x - 1, j, k) - f_\alpha(N_x - 2, j, k).$$

On the surface of the sphere, Eqs. (1.9), (1.10), (1.11b), and (2.4) proposed in this work are used to update the boundary conditions for f_α 's. Only the LBE nineteen-velocity model is used to simulate the flow over a sphere.




FIG. 12. Schematic for computational domain in the uniform flow past a sphere.

Figure 13 shows the velocity profile $u_x(y)$ based on a series of computations carried out for several values of the radius $R = 3.0, 3.2, 3.4, 3.6, 3.8$ and 4.0 for $H/R = 10$ at $\text{Re} = 10$. The results are obtained with $\tau = 0.7$. Fig. 14 compares the axial velocity profile (at $y = z = 0$) for the same set of parameters. It is worth noting that the present LBE computation does not have sufficient resolution for the given Reynolds number. Yet the velocity profiles agree with each other accurately. The fact that we have obtained a spatially accurate solution over a range of radii strongly suggests that the present boundary condition treatment for curved geometry in the LBE method is capable of handling more complex geometries while maintaining good accuracy.

4. Concluding Remarks. Three 3-D LBE models, including the fifteen-velocity, the nineteen-velocity, and the twenty-seven-velocity model, have been assessed in terms of efficiency, accuracy, and robustness in lid-driven cavity flow. While accurate 3-D results can be obtained by using various LBE models, the nineteen-velocity model is found to be the best for the cases investigated. The fifteen-velocity model exhibits velocity




FIG. 13. Uniform flow over a sphere at $Re = 10$, $\tau = 0.7$, and $H/R = 10$. Comparison of the normalized velocity profiles $u_x(y)/U$ at $x = z = 0$ for various values for the sphere radius $R = 3.0$ (\times), 3.2 (\triangle), 3.4 ($+$), 3.6 (\diamond), 3.8 (dashed line), and 4.0 (solid line).




FIG. 14. Uniform flow over a sphere at $Re = 10$, $\tau = 0.7$, and $H/R = 10$. Comparison of the normalized centerline at velocity profiles $u_x(x)/U$ (at $y = z = 0$) for various values for the sphere radius $R = 3.0$ (dash-dot line), 3.2 (dotted line), 3.4 (dashed line), 3.6 (dash dot dot dot line), 3.8 (long dashed line), and 4.0 (solid line).

oscillations and is prone to computational instability. The more complicated twenty-seven-velocity model does not necessarily give more accurate results than the nineteen-velocity model with the same spatial resolution. In this study, we have also modified the boundary condition treatment for LBE method proposed by Filippova & Hänel [8] and Mei *et al.* [20] when the fraction of the intersected link on the boundary Δ is greater than one half. This improves the computational stability when Δ is close to 1 and τ close to $1/2$.

The simulations for flows in a square duct and in a circular pipe indicate that the current boundary

condition treatment for curved geometries results in second-order accuracy in 3-D flows. The velocity profiles for flow over a sphere show good self-consistency of the solution over a range of sphere radii used.

Acknowledgments. This work is partially supported by NASA Langley Research Center under the program of Innovative Algorithms for Aerospace Engineering Analysis and Optimization. R. Mei also acknowledges partial support of the Engineering Research Center (ERC) for Particle Science & Technology at the University of Florida, the National Science Foundation (EEC-9402989), and Industrial partners of the ERC. W. Shyy acknowledges partial support of AFOSR and Eglin AFB. We would like to thank Dr. O. Filipova and Prof. D. Hänel for helpful discussions, and are grateful to Dr. R. Rubinstein for his careful reading of the manuscript.

Appendix A. 3-D LBE Models.

The D3Q15 model has the following set of discrete velocities:

$$(A.1) \quad \mathbf{e}_\alpha = \begin{cases} (0, 0, 0), & \alpha = 0, & \text{rest particle,} \\ (\pm 1, 0, 0)c, (0, \pm 1, 0)c, (0, 0, \pm 1)c, & \alpha = 1, 2, \dots, 6, & \text{group I,} \\ (\pm 1, \pm 1, \pm 1)c, & \alpha = 7, 8, \dots, 14, & \text{group III,} \end{cases}$$

and the weighting factor w_α is [24]:

$$(A.2) \quad w_\alpha = \begin{cases} 2/9, & \alpha = 0, & \text{rest particle,} \\ 1/9, & \alpha = 1, 2, \dots, 6, & \text{group I,} \\ 1/72, & \alpha = 7, 8, \dots, 14, & \text{group III.} \end{cases}$$

The D3Q19 model has the following set of discrete velocities:

$$(A.3) \quad \mathbf{e}_\alpha = \begin{cases} (0, 0, 0), & \alpha = 0, & \text{rest particle,} \\ (\pm 1, 0, 0)c, (0, \pm 1, 0)c, (0, 0, \pm 1)c, & \alpha = 1, 2, \dots, 6, & \text{group I,} \\ (\pm 1, \pm 1, 0)c, (0, \pm 1, \pm 1)c, (\pm 1, 0, \pm 1)c, & \alpha = 7, 8, \dots, 18, & \text{group II,} \end{cases}$$

and the weighting factor w_α is [14]:

$$(A.4) \quad w_\alpha = \begin{cases} 1/3, & \alpha = 0, & \text{rest particle,} \\ 1/18, & \alpha = 1, 2, \dots, 6, & \text{group I,} \\ 1/36, & \alpha = 7, 8, \dots, 18, & \text{group II.} \end{cases}$$

The D3Q27 model has the following discrete velocities:

$$(A.5) \quad \mathbf{e}_\alpha = \begin{cases} (0, 0, 0), & \alpha = 0, & \text{rest particle,} \\ (\pm 1, 0, 0)c, (0, \pm 1, 0)c, (0, 0, \pm 1)c, & \alpha = 1, 2, \dots, 6, & \text{group I,} \\ (\pm 1, \pm 1, 0)c, (0, \pm 1, \pm 1)c, (\pm 1, 0, \pm 1)c, & \alpha = 7, 8, \dots, 18, & \text{group II,} \\ (\pm 1, \pm 1, \pm 1)c, & \alpha = 19, 20, \dots, 26, & \text{group III,} \end{cases}$$

and the weighting factor w_α is [14]:

$$(A.6) \quad w_\alpha = \begin{cases} 8/27, & \alpha = 0, & \text{rest particle,} \\ 2/27, & \alpha = 1, 2, \dots, 6, & \text{group I,} \\ 1/54, & \alpha = 7, 8, \dots, 18, & \text{group II,} \\ 1/216, & \alpha = 19, 20, \dots, 26, & \text{group III.} \end{cases}$$

In the above, $c = \delta x / \delta t$, δx and δt are the lattice constant and the time step size, respectively. The lattice structures for the D3Q15 and D3Q19 models are shown in Fig. 15.




FIG. 15. Discrete velocity sets $\{e_\alpha\}$ for the $D3Q15$ (left) and $D3Q19$ (right) models.

REFERENCES

- [1] T. ABE, *Derivation of the lattice Boltzmann method by means of the discrete ordinate method for the Boltzmann equation*, J. Computat. Phys., 131 (1997), pp. 241–246.
- [2] O. BEHREND, *Solid boundaries in particle suspension simulations via lattice Boltzmann method*, Phys. Rev. E, 52 (1995), pp. 1164–1175.
- [3] R. BENZI, S. SUCCI, AND M. VERGASSOLA, *The lattice Boltzmann equation: Theory and applications*, Phys. Rep., 222 (1992), pp. 145–197.
- [4] P.L. BHATNAGAR, E.P. GROSS, AND M. KROOK, *A Model for Collision Processes in Gases. I. Small Amplitude Processes in Charged and Neutral One-Component Systems*, Phys. Rev., 94 (1954), pp. 511–525.
- [5] H. CHEN, S. CHEN, AND W.H. MATTHAEUS, *Recovery of the Navier-Stokes equations using a lattice-gas Boltzmann method*, Phys. Rev. A, 45 (1992), pp. R5339–R5342.
- [6] S. CHEN AND G.D. DOOLEN, *Lattice Boltzmann method for fluid flows*, Annu. Rev. Fluid Mech., 30 (1998), pp. 329–364.
- [7] S. CHEN, D. MARTÍNEZ, AND R. MEI, *On boundary conditions in lattice Boltzmann method*, Phys. Fluids, 8 (1996), pp. 2527–2536.
- [8] O. FILIPPOVA AND D. HÄNEL, *Grid refinement for lattice-BGK models*, J. Computat. Phys., 147 (1998), pp. 219–228.
- [9] C.A.J. FLETCHER, *Computational Techniques for Fluid Dynamics*, Vols. I & II (Springer-Verlag, New York, 1988).
- [10] I. GINZBOURG AND P.M. ALDER, *Boundary flow condition analysis for the three-dimensional lattice Boltzmann model*, J. Phys. II France, 4 (1994), pp. 191–214.
- [11] I. GINZBOURG AND D. D’HUMIÈRES, *Local second-order boundary methods for lattice Boltzmann models*, J. Stat. Phys., 84 (1996), pp. 927–971.
- [12] X. HE AND G. DOOLEN, *Lattice Boltzmann method on curvilinear coordinates system: Flow around a circular cylinder*, J. Computat. Phys., 134 (1997), pp. 306–315.
- [13] X. HE AND L.-S. LUO, *A priori derivation of the lattice Boltzmann equation*, Phys. Rev. E, 55 (1997), pp. R6333–R6336.
- [14] ———, *Theory of the lattice Boltzmann method: From the Boltzmann equation to the lattice Boltzmann*

- equation*, Phys. Rev. E, 56 (1997), pp. 6811–6817.
- [15] X. HE, Q. ZOU, L.-S. LUO, AND M. DEMBO, *Analytic solutions and analysis on non-slip boundary condition for the lattice Boltzmann BGK model*, J. Stat. Phys., 87 (1997), pp. 115–136.
 - [16] D. KANDHAI, A. KOPONEN, A. HOEKSTRA, M. KATAJA, J. TIMONEN, AND P.M.A. SLOOT, *Implementation aspects of 3D lattice-BGK: Boundaries, accuracy, and a new fast relaxation method*, J. Computat. Phys., 150 (1999), pp. 482–501.
 - [17] A.J.C. LADD, *Numerical simulation of particular suspensions via a discretized Boltzmann equation. Part 2. Numerical results*, J. Fluid Mech., 271 (1994), pp. 311–339.
 - [18] P. LALLEMAND AND L.-S. LUO, *Theory of the lattice Boltzmann method: Dispersion, dissipation, isotropy, Galilean invariance, and stability*, Phys. Rev. E, 61 (2000), pp. 6546–6562.
 - [19] L.-S. LUO, *Analytic solutions of linearized lattice Boltzmann equation for simple flows*, J. Stat. Phys., 88 (1997), pp. 913–926.
 - [20] R. MEI, L.-S. LUO, AND W. SHYY, *An accurate curved boundary treatment in the lattice Boltzmann method*, J. Computat. Phys., 155 (1999), pp. 307–330.
 - [21] R. MEI AND W. SHYY, *On the finite difference-based lattice Boltzmann method in curvilinear coordinates*, J. Computat. Phys., 143 (1998), pp. 426–448.
 - [22] D.R. NOBLE, S. CHEN, J.G. GEORGIADIS, AND R.O. BUCKIUS, *A consistent hydrodynamic boundary condition for the lattice Boltzmann method*, Phys. Fluids, 7 (1995), pp. 203–209.
 - [23] R. PEYRET AND T.D. TAYLOR, *Computational Technique for Fluid Dynamics*, Vol. II (Springer-Verlag, New York, 1983).
 - [24] Y.H. QIAN, D. D’HUMIÈRES, AND P. LALLEMAND, *Lattice BGK models for Navier-Stokes equation*, Europhys. Lett., 17 (1992), pp. 479–484.
 - [25] Y.H. QIAN, S. SUCCI, AND S.A. ORSZAG, *Recent advances in lattice Boltzmann computing*, in *Annual Reviews of Computational Physics*, Vol. III, edited by D. STAUFFER (World Scientific, Singapore, 1995), pp. 195–242.
 - [26] J. SALOM, *Numerical Simulation of Convection Phenomena Based on Domain Decomposition Techniques and Experimental Validation*, Ph.D. Dissertation, Universitat Politècnica de Catalunya, Spain, 1999.
 - [27] W. SHYY, *Computational Modeling for Fluid Flow and Interfacial Transport*, corrected printing (Elsevier, Amsterdam, 1997).
 - [28] F.M. WHITE, *Viscous Fluid Flow* (McGraw Hill, New York, 1974).
 - [29] D.P. ZIEGLER, *Boundary conditions for lattice Boltzmann simulations*, J. Stat. Phys., 71 (1993), pp. 1171–1177.
 - [30] Q. ZOU AND X. HE, *On pressure and velocity boundary conditions for the lattice Boltzmann BGK model*, Phys. Fluids, 9 (1997), pp. 1591–1598.

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 2002		3. REPORT TYPE AND DATES COVERED Contractor Report
4. TITLE AND SUBTITLE Lattice Boltzmann method for 3-D flows with curved boundary			5. FUNDING NUMBERS C NAS1-97046 WU 505-90-52-01	
6. AUTHOR(S) Renwei Mei, Wei Shyy, Dazhi Yu, and Li-Shi Luo				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) ICASE Mail Stop 132C NASA Langley Research Center Hampton, VA 23681-2199			8. PERFORMING ORGANIZATION REPORT NUMBER ICASE Report No. 2002-17	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Langley Research Center Hampton, VA 23681-2199			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA/CR-2002-211657 ICASE Report No. 2002-17	
11. SUPPLEMENTARY NOTES Langley Technical Monitor: Dennis M. Bushnell Final Report Journal of Computational Physics, Vol. 161, pp. 680-699, 2000.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified-Unlimited Subject Category 34 Distribution: Nonstandard Availability: NASA-CASI (301) 621-0390			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) In this work, we investigate two issues that are important to computational efficiency and reliability in fluid dynamics applications of the lattice Boltzmann equation (LBE): (1) Computational stability and accuracy of different lattice Boltzmann models and (2) the treatment of the boundary conditions on curved solid boundaries and their 3-D implementations. Three athermal 3-D LBE models (D3Q15, D3Q19, and D3Q27) are studied and compared in terms of efficiency, accuracy, and robustness. The boundary treatment recently developed by Filippova and Hänel and Mei et al. in 2-D is extended to and implemented for 3-D. The convergence, stability, and computational efficiency of the 3-D LBE models with the boundary treatment for curved boundaries were tested in simulations of four 3-D flows: (1) Fully developed flows in a square duct, (2) flow in a 3-D lid-driven cavity, (3) fully developed flows in a circular pipe, and (4) a uniform flow over a sphere. We found that while the fifteen-velocity 3-D (D3Q15) model is more prone to numerical instability and the D3Q27 is more computationally intensive, the D3Q19 model provides a balance between computational reliability and efficiency. Through numerical simulations, we demonstrated that the boundary treatment for 3-D arbitrary curved geometry has second-order accuracy and possesses satisfactory stability characteristics.				
14. SUBJECT TERMS lattice Boltzmann method, boundary condition for curved geometries, accuracy, 3-D flows, Navier-Stokes equations			15. NUMBER OF PAGES 23	
			16. PRICE CODE A03	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT	